



F SERIES

W4-1798S



- IT'S THE SIZE OF 4.5"
- FULL RANGE FREQUENCY DESIGN
- WIDE DISPERSION PERFORMANCE
- FLAT ALUMINUM SANDWICH CONE
- NEODYMIUM MAGNET SYSTEM
- LOW 2nd AND 3rd DISTORTION
- IT'S GOOD FOR FULL RANGE OR MID-RANGE APPLICATION

4" SANDWICH FULL RANGE / MIDRANGE



DIAPHRAGM MTL	Sandwich
SURROUND MTL	Foam Rubber
NOMINAL IMPEDANCE	4 Ω
DCR IMPEDANCE	3.6 Ω
SENSITIVITY 1W/1M	87 dB
FREQUENCY RESPONSE	60-20K Hz
FREE AIR RESONANCE	60 Hz
VOICE COIL DIAMETER	49.5 mm
AIR GAP HEIGHT	12 mm
RATED POWER INPUT	40 W
MAXIMUM POWER INPUT	80 W
FORCE FACTOR, BL	5.75 TM
TYPE OF MAGNET	Neodymium
MOVING MASS	9.98 g
FERROFLUID ENHANCED	No
SUSPENSION COMPLIANCE	847.55 μMN^{-1}
EFFECTIVE PISTON AREA	0.0078 M ²
Levc	0.009 mH
Zo	19 Ω
Xmax	3 mm
Vas	7.42 Litr
Qts	0.30
Qms	1.61
Qes	0.37

TB SPEAKERS

VOICE: 886.2.26570282 FAX: 886.2.26580166
E-MAIL: info@tb-speaker.com